


Tool



The Path to Ultimate Sustainability



© Passivhaus Institut

Global Climate Specificity




Illustration © Passive House Institute

Climate-Specific Requirements

Climate zone according to PHPP	Opaque envelope ¹ against...				Windows (including exterior doors)				Ventilation		
	...ground	...ambient air			Overall ⁴			Glazing ⁵	Solar load ⁶	Min. heat recovery rate ⁷	Min. humidity recovery rate ⁸
	Insulation	Exterior insulation	Interior insulation ²	Exterior paint ³	Max. heat transfer coefficient ($U_{D/W,installed}$)			Solar heat gain coefficient (g-value)	Max. specific solar load during cooling period		
	Max. heat transfer coefficient (U-value)			Cool colours						[kWh/m ² a]	%
	[W/(m ² K)]			-	[W/(m ² K)]	-					
					  						
Arctic	Determined in PHPP from project specific heating and cooling degree days against ground.	0.09	0.25	-	0.45	0.50	0.60	$U_g - g*0.7 \leq 0$	100	80%	-
Cold		0.12	0.30	-	0.65	0.70	0.80	$U_g - g*1.0 \leq 0$		80%	-
Cool-temperate		0.15	0.35	-	0.85	1.00	1.10	$U_g - g*1.6 \leq 0$		75%	-
Warm-temperate		0.30	0.50	-	1.05	1.10	1.20	$U_g - g*2.8 \leq -1$		75%	-
Warm		0.50	0.75	-	1.25	1.30	1.40	-		-	-
Hot		0.50	0.75	Yes	1.25	1.30	1.40	-		-	60 % (humid climate)
Very hot		0.25	0.45	Yes	1.05	1.10	1.20	-		-	60 % (humid climate)


PHIUS+

United States




- Passive House Institute U.S., Chicago, IL
- Local raters and tie-in with other certifications
- New sovereign standard for the U.S.
- Climate zone specific

U.S. Climate Specificity



Energy Modeling

WUFI® Passive



Passive House in 90 Seconds





Basic Concept

Conservation first

➔ Minimize losses

➔ Maximize (free) gains

Active vs. Passive



Active: 25-125 kBtu/(sf yr)


85 - 450 kWh/(m² a), typically found in the U.S.

Passive: 4.75 kBtu/(sf yr)


15kWh/(m² a), maximum target

Energy Footprint

- Heating (active)
- Hot water (active)
- Cooling (active)
- Household Electricity
- Heat & hot water (passive)



Code



Passive House

- ➔ up to 95% less heating energy
- ➔ 50 to 75% less total energy


Learning from the BioHaus

Waldsee BioHaus, North America's first certified Passive House


Average energy use since 2006: 33kWh/(m² yr), or 10,500 Btu/(sf yr)



Performance Comparison



Understanding Energy Flow



120 kWh/ (m² a) or 38.1 kBtu/(sf yr) • Passive House Target • 15 kWh/ (m² a) or 4.75 kBtu/(sf yr)

Understanding Energy Flow

Passive House takes care of energy performance.

Other systems and certifications are recommended to control:

- **Environmentally and people friendly use of resources**
- **Operation, facility management**
- **Indoor environmental quality**

Case Study 1


Impact of the

Passive House Standard

State of South Dakota, 2013/14




SDSU, Brookings, South Dakota



intep

Jackrabbit Grove Residence Hall



South Dakota State University campus in Brookings, South Dakota
Building E, 2012

LEED Silver, 95 rooms, 190 tenants


Jackrabbit Grove Residence Hall



Project

- Analysis of the design and construction of the Base Building
- Analysis of the construction cost of the Base Building
- Creation of a Passive House version of the Base Building
- PHPP energy modeling
- Life cycle costing
- Evaluation and Recommendations
- Conclusion and Benefits



High-Performance Building Envelope




	Base Building	Passive House Building
Exterior Walls	R-16 (h sf °F/ Btu)	R-34 (h sf °F/ Btu)
Roof	R-70 (h sf °F/ Btu)	R-70 (h sf °F/ Btu)
Slab	R-3 (h sf °F/ Btu)	R-27 (h sf °F/ Btu)
Windows, Ext. Doors	U- 0.41 (Btu/ h sf °F) SHCG-0.27	U- 0.12 (Btu/ h sf °F) SHCG-0.50
Thermal Bridges	Significant	Free
Airtightness	ACH ₅₀ : 3.0 1/h (est.)	ACH₅₀: ≤ 0.6 1/h (field tested)
Ventilation w/ HR	51% HR-Efficiency 0.45 Wh/ m ³ Electr. Eff.	87% HR-Efficiency 0.45 Wh/ m ³ Electr. Eff.
Heating/ Cooling	District heating/cooling	District heating/cooling

→ Opportunity for on-site HVAC system




Thermal Bridge Free Assemblies



Thermal Bridge Free Details




Heat Flow Comparison




- ➔ Heat Load Reduction 95%!
- ➔ Poor R-values
- ➔ Poor components
- ➔ Major thermal bridges


Heat Loss Comparison




Energy Consumption Comparison




Energy Flow Comparison




- Focus on plug loads
- Focus on domestic hot water






Base Building



Passive House Building



Carbon Emissions Comparison



Cost Comparison

Building Component	Base Building	Passive House Building	Difference
Structural Building Concrete + Steel + Masonry Systems	\$2,015,796	\$2,015,796	\$0
Rough + Finish Carpentry	\$230,339	\$230,339	\$0
Roofing, Moisture & Thermal Protection	\$334,957	+\$634,957	+\$300,000
Glass & Glazing/ Door + Hardware	\$611,076	+\$1,067,076	+\$456,000
Drywall Steel Stud Framing	\$587,489	\$587,489	\$0
Interior Finishes	\$451,441	\$451,441	\$0
Specialties & Accessories	\$84,406	\$84,406	\$0
Elevators	\$95,000	\$95,000	\$0
Plumbing Systems + Fire Suppressions System	\$762,800	\$762,800	\$0
HVAC Systems	\$518,650	\$468,650	(\$50,000)
Electrical Systems	\$683,675	\$683,675	\$0
Earthwork Excavation	\$122,590	\$122,590	\$0
Building Investment Cost Total	\$6,498,219	\$7,196,046	\$697,827

➔ Construction cost increase of approx. 10.5%

Life Cycle Cost Comparison

Annual Annualized Cost Comparison w/o HVAC system reduction



- Construction Cost
- Management & Insurance
- Security
- Cleaning
- Inspection & Maintenance
- Utilities & Disposal
- Repair
- Refurbishments

Calculation Parameters

The following parameters were used for calculation of the life cycle and operating cost:

- Duration of assessment: 50 years
- Inflation:
 - Construction (nominal) 3.00%
 - Management and services (nominal) 1.00%
 - Utilities and waste (nominal) 3.00%
 - Interest rate (nominal) 4.00%
 - Energy and telecommunication
 - Water (m³) \$ 0.83
 - Waste water (m³) \$ 1.11
 - District Heat (kWh) \$ 0.05
 - District Cooling (kWh) \$ 0.05
 - Electricity (kWh) \$ 0.07

➔ Annual Annuitized Cost Reduction of approx. 3%